

Eni i-Sigma top 10W-40



APPLICATIONS

Eni i-Sigma top 10W-40 is a multigrade high performance synthetic technology lubricant suitable for the lubrication of supercharged engines operating in severe conditions with fuel saving features and which allows the maximum change intervals.

The product is indicated for most manufacturers in the sector.

CUSTOMER ADVANTAGES


- The top quality bases used and the special additivation technology guarantees a constant performance even with extended change intervals.
- The SAE grade (10W-40) makes the product suitable for any climatic situation, allowing start-up even under critical low temperature conditions.
- The dispersant-detergent properties and the neutralizing power against acidic combustion products guarantees exceptional piston cleanliness and dispersion of solid combustion or degradation products, avoiding precipitation and subsequent formation of deposits.
- The product guarantees excellent oxidation resistance even in prolonged operation at high temperatures. Its antioxidant, anti-rust and anti-wear characteristics are suitable for severe operation and provide long change intervals.
Oxidation is effectively inhibited, ensuring constant viscosity in the life time of use. Metallic surfaces are effectively protected against wear and corrosion ensuring and maintaining maximum engine efficiency over time.

SPECIFICATIONS

- ACEA E4, E7
- API CI-4
- Cummins CES 20078
- Deutz DQC III-18 (Approved)
- MACK EO-N (Approved)
- MAN M 3277 (Approved)
- MB-Approval 228.5
- MTU type 3 (Approved)



Eni i-Sigma top 10W-40



- Renault VI RLD-2 (Approved)
- Volvo VDS-3 (Approved)

CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	868
Viscosity at 100°C	ASTM D 445	mm ² /s	14.7
Viscosity at 40°C	ASTM D 445	mm ² /s	98
Viscosity Index	ASTM D 2270	-	156
Viscosity at -25°C	ASTM D 5293	mPa·s	6124
Pour point	ASTM D 5950	°C	-42
Flash point COC	ASTM D 92	°C	226
B. N.	ASTM D 2896	mg KOH/g	12.5

