



APPLICATIONS

Eni Multitech CT 60 is a special lubricant suitable for use in Caterpillar machines. It can be used for lubrication of transmissions, final drives, differentials, winches, clutches, gears and bearings.

CUSTOMER ADVANTAGES

- **Eni Multitech CT 60** has a balanced formulation which ensures the longest duration of friction materials in Powershift gearboxes, and eliminates brake chatter in applications with wet brakes.
- Meets the severe requirements of the Caterpillar TO-4 specification, which includes specific frictional requirements and antiwear properties.
- Even if it is not intended for engine applications, **Eni Multitech CT 60** supports engine oil performance API CF/CF-2, keeping machinery safe from any risk of failure due to misuse.
- Although it is not officially approved by Komatsu, **Eni Multitech CT 60** is suitable for use in all applications where the manufacturer requires a KES 07.868.1 performance level.

SPECIFICATIONS

- Caterpillar TO-4
- TREMEC/TTC
- Eaton Vickers I-280 S
- Vickers M-2950-S





CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	910
Viscosity at 100°C	ASTM D 445	mm ² /s	25.3
Viscosity Index	ASTM D 2270	-	100
Flash point COC	ASTM D 92	°C	240
Pour point	ASTM D 5950	°C	-15
Calcium	ASTM D 4951	% (m/m)	
Zinc	ASTM D 4951	% (m/m)	

