



## APPLICATIONS

**Eni Grease 15** is an anhydrous calcium grease, green coloured and stringy appearance.

Endowed with a considerable adhesiveness to the surfaces where it is applied, **Eni Grease 15** effectively resists to the vibrations that tend to come off the grease; feature that makes it ideal for the lubrication of vehicle frames.

**Eni Grease 15** combines the normal lubrication functions with those of protection against wear necessary for the perfect working and conservation of the organs on which it is applied.

It is also provided with water-repellent characteristics, that allow its use in wet environments and in contact with water.

## CUSTOMER ADVANTAGES

- Excellent metal surfaces adhesivity
- High protection against corrosion and wear of metal, ferrous and non-ferrous.

## SPECIFICATIONS - APPROVALS

- ASTM D 4950 LA
- ISO 12924 L-XBBGA 1
- DIN 51825 K 1G -20





## CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	-	-	stringy homogeneous
Colour	-	-	green
Base oil type	-	-	mineral
Base Oil Viscosity at 40°C	ASTM D 7042	mm <sup>2</sup> /s	100
Thickener type	-	-	anhydrous calcium
Consistency (NLGI grade)	-	-	1
Dropping point	ASTM D 566	°C	145
Penetration at 60 double stroke	ASTM D 217	dmm	325
Oil separation	ASTM D 1742	% (m/m)	<6.5
Copper corrosion	ASTM D 4048	-	1a
Temperature range	-	°C	-20/+80



eni