



APPLICATIONS

Eni Grease 30 is a smooth-textured, yellow, lithium-based grease, designed and developed as a multipurpose grease for the general lubrication of motor vehicles: bearings, wheel hubs, water pump, dynamo, motor starting, chassis, etc.

Endowed of strong mechanical and chemical stability, maintain its characteristics unaltered even after intense and prolonged mechanical and thermal stresses.

Thanks to the special adhesiveness to the surfaces where it is applied, **Eni Grease 30** offers a good resistance to vibrations that tend the detachment and water repellency characteristics, that allow its use in a humid environment.

The high dropping point allows the utilize of the product without problems in a wide temperature range.

CUSTOMER ADVANTAGES

- Multi-purpose product, simplifies the management of stored products
- Can be used for lubrication and protection of ferrous and non-ferrous components

SPECIFICATIONS - APPROVALS

- ISO 12924 L-XBCHA 2
- DIN 51825 K 2K -20
- ASTM D 4950 GB





CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	-	-	homogeneous smooth-textured
Colour	-	-	brown yellow
Base oil type	-	-	mineral
Base Oil Viscosity at 40°C	ASTM D 445	mm ² /s	100
Thickener type	-	-	lithium
Consistency (NLGI grade)	ASTM D 217	-	2
Dropping point	ASTM D 566	°C	200
Penetration at 60 double stroke	ASTM D 217	dmm	280
Oil separation	ASTM D 1742	% (m/m)	<2
Temperature range	-	°C	-20/+120



eni