

# Eni MX 3318

dispersant additive



**Eni MX 3318** is a chlorine free, low molecular weight, bis-succinimide, ashless dispersant typically used in two-Stroke engine lubricants.

## APPLICATIONS

- **Eni MX 3318** has excellent results in lubricity tests as well as in smoke control ones. It shows very good antirust characteristics and an excellent control of low temperature sludge deposits.
- Eni Mx 3318 is compatible with a wide range of additives and solvents.
- Treat rates depend upon application and performance requirements.

## TECHNICAL DATA

	Method	Unit	Values		Typical
			Min	Max	
Appearance		-			limpid liquid
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>			930
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	100	270	
Flash point PM	ASTM D 93	°C	150		
B. N.	ASTM D 2896	mg KOH/g	25	45	
Nitrogen	ASTM D 5291	% (m/m)	1.23	1.68	
Oil content	Calculated	% (m/m)			45

## HANDLING INFORMATION

- storage: the maximum handling and unloading temperature is 60°C; it is recommended that, for long term storage, the temperature should not exceed 50°C; shelf life is 24 months at ambient temperature and in adequate storage, conditions (containers kept closed and set upright on pallets with bungs on top. In case of open-air storage, drums on the top pallet must have a waterproof lid).
- transport information: the product is classified as not dangerous as far as naval, rail and road transportation is concerned.
- safety & regulatory information: please see safety data sheet in <https://msds.eni.com/AthosSDS/>

## PACKAGING

- Bulk
- IBC (1000 litres)
- Drums (200 litres)



# Eni MX 3318

dispersant additive



## PRODUCTION SITE

Domus Chemical S.p.A.  
Via Mazzini, 1  
24066 Pedrengo (BG)  
ITALY



eni