



APPLICATIONS

Eni Grease LCX 1.5/460 is a lithium complex grease, formulated with synthetic base oil of viscosity ISO VG 460 that allow the grease to operate at very low temperatures.

The particular combination of anti-wear, EP, anticorrosive and anti-oxidant additives guarantees excellent performance in severe operating conditions such as high loads and in presence of vibrations.

In addition, the synthetic base gives a high thermal and oxidative stability over time, allowing a reduction of downtime cases and maintenance costs.

Eni Grease LCX 1.5/460 is specifically indicated for slow reducers operating in humid environments, with high loads and high temperatures such as used in steel, paper and glass industries and in the lubrication of the main shaft bearings and the bearings which regulate the propeller pitch and the swinging of the wind blades.

Eni Grease LCX 1.5/460 is suitable for the lubrication of excavating machines and TBM (Tunnel Boring Machine).

CUSTOMER ADVANTAGES

- Suitable for applications at high and low temperature thanks to the nature of the synthetic base and the very high dropping point
- Extension of service life and relubrication intervals, even in the presence of strong mechanical and thermal stresses
- Excellent adhesiveness and resistance to water washout. Can be used in humid environments and in the presence of water
- Good loads resistance
- High anti-rust and anti-corrosion protection and compatibility with all types of metals both ferrous and non-ferrous

SPECIFICATIONS - APPROVALS

- DIN 51825 KPHC 1,5R -40
- ISO 12924 L-XDFHB 1,5





CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	-	-	smooth-textured homogeneous
Colour	-	-	gray/beige opaque
Thickener type	-	-	litio complesso
Consistency (NLGI grade)	ASTM D 217	-	1.5
Penetration at 60 double stroke	ASTM D 217	dmm	300
Base oil type	-	-	sintetico
Base Oil Viscosity at 40°C	ASTM D 445	mm ² /s	460
Dropping point	ASTM D 566	°C	290
Corrosion	ASTM D 1743	-	supera
Copper corrosion	ASTM D 4048	-	1a
Timken OK load	ASTM D 2509	lbs	>45
4 Balls weld load	ASTM D 2596	kg	315
Temperature range	-	°C	-40/+180



eni