

# Eni i-Sea outboard 4T 10W-40



## APPLICATIONS

**Eni i-Sea outboard 4T 10W-40** is a universal lubricant for 4-stroke outboard motors.

## CUSTOMER ADVANTAGES

- It is formulated with high technology components that allow the engine to express its maximum performance, while protecting it from mechanical wear and saline corrosion, even in case of prolonged inactivity.
- It keeps the engine clean avoiding the formation of carbon deposits to ensure maximum reliability of operation and long life to all lubricated parts.
- It effectively contrasts the adverse effects of lubricant dilution in the fuel, which are particularly significant in the case of prolonged operation of the engine at minimum speeds.
- It allows to minimize the formation of sludge in the engine avoiding the risk of occlusion of the filters.
- It has been successfully subjected to the most stringent performance tests (the product achieves a NMMA FC-W® performance level).

## SPECIFICATIONS

- API SM
- JASO MA T903:2011
- NMMA FC-W (CAT) (Approved)



# Eni i-Sea outboard 4T 10W-40



## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	861
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	13.8
Viscosity Index	ASTM D 2270	-	160
Viscosity at -25°C	ASTM D 5293	mPa·s	4760
Flash point COC	ASTM D 92	°C	220
Pour point	ASTM D 5950	°C	-30

