



## APPLICATIONS

**Eni Arnica V** is a biodegradable hydraulic fluid obtained from esters of vegetable origin particularly selected and refined, intended for those applications where the problem of environmental pollution is prevalent and where there is a risk of accidental spills from machinery towards the environment.

The high viscosity index allows their use in a particularly wide range of ambient temperatures. Moreover compared to other product classes, it has a higher flash point, a useful safety feature in the workplace.

**Eni Arnica V** is biodegradable over 60% according to OECD test 301B.

We recommend the use of the product in systems where the maximum internal temperature of the hydraulic circuit does not exceed 60°C.

In exceptional cases and for short periods of time the temperature up to 70°C is tolerated.

## CUSTOMER ADVANTAGES

- Excellent demulsibility. Effectively prevents the formation of stable emulsion with water avoiding the depletion of the lubricant
- Excellent corrosion and rust protection. It effectively providing the protection of metallic part present in the circuit
- Good anti-foam characteristic preventing the consequent malfunctioning of the hydraulic plants
- Compatible with seal materials generally used in hydraulic systems
- Excellent anti-wear property proved by the FZG test > 12th stage

## SPECIFICATIONS - APPROVALS

- ISO 15380 HETG
- WGK 1





## CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	ASTM D 4176/1	-	clear liquid
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	920
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	32
Flash point COC	ASTM D 92	°C	184
Pour point	ASTM D 97	°C	-33



eni