

Eni MX 3323

bis-succinimide dispersant additive



Eni MX 3323 is a chlorine free, bis-succinimide, ashless dispersant typically used in crankcase engine lubricants.

APPLICATIONS

- **Eni MX 3323** provides excellent low temperature sludge and varnish control coupled with good antirust characteristics;
- **Eni MX 3323** has a specific application in gasoline engine lubricants;
- Treat rates depend upon application and performance requirements.

FURTHER INFORMATION

- **storage:** the maximum handling and unloading temperature is 60°C; it is recommended that, for long term storage, the temperature should not exceed 50°C; shelf life is 24 months at ambient temperature and in adequate storage conditions (containers kept closed and set upright on pallets with bungs on top. In case of open-air storage, drums on the top pallet must have a waterproof lid);
- **transport information:** the product is classified as not dangerous as far as naval, rail and road transportation is concerned;
- **safety & regulatory information:** please see safety data sheet in <https://msds.eni.com/AthosSDS/>;
- for commercial information please make contact with: **eniadditives@eni.com**.

TECHNICAL DATA

	Method	Unit	Values	
			Min	Max
Appearance		-	dark limpid liquid	
Density at 15°C	ASTM D 4052	kg/m ³	920	
Viscosity at 100°C	ASTM D 445	mm ² /s	220	350
Flash point PM	ASTM D 93	°C	150	
B. N.	ASTM D 2896	mg KOH/g	25	37
Nitrogen	ASTM D 5291	% (m/m)	1.08	1.45
Oil content	Calculated	% (m/m)	47	



Eni MX 3323

bis-succinimide dispersant additive



PACKAGING

Eni MX 3323 is available in:

- Bulk
- IBC
- Drums

PRODUCTION SITE

Domus Chemical S.p.A.
via Mazzini, 1
24066 Pedrengo (BG)
ITALY



eni